

NOTES: UNLESS OTHERWISE SPECIFIED

1. CONFIGURATIONS WILL BE VALIDATED BY SALES REPRESENTATIVE.

REV	ECR	DESCRIPTION	BY	DATE	CHECKED
B	1800 1835 2365	DRAWING FORMAT & NOTES UPDATE	K.T.	03/31/2016	A.J.
B.3	-	ADDED CALLOUTS	K.T.	08/20/2018	A.J.

TYPE

M	OM1 Multimode 62.5 μm
N	OM2 Multimode 50 μm
J	OM3 Multimode 50 μm
H	OM4 Multimode 50 μm
E	OM5 Multimode 50 μm
S	OS2 Single-mode
T	OS2 Bend Insensitive Single-mode

POLISH

P	PC
S	SPC
A	APC
U	UPC
B	APC/UPC

FIBER COUNT

01	Simplex
02	Duplex
04	4 Fibers
↓	
96	96 Fibers
44	144 Fibers
88	288 Fibers

JACKET

L	LSZH 2 mm
K	LSZH 3 mm
U	OFNP 1.6 mm
W	OFNP 1.8 mm
Q	OFNP 2 mm
P	OFNP 3 mm
H	OFNP 4.8 mm

B	900 μm
T	OFNR 1.6 mm
V	OFNR 1.8 mm
S	OFNR 2 mm
R	OFNR 3 mm
G	OFNR 4.8 mm

CABLE TYPE

D	Outdoor
F	Fan Out
G	MIC 250 μm
I	Indoor
O	Indoor/Outdoor
T	Flat Drop Tonable
V	Aerial

A	Armored
N	MicroArmored
B	OSP Armored
C	I/O Armored
Q	I/O MicroArmored
H	MIC 250 μm Armored

CONNECTOR 1 / CONNECTOR 2

LB	LC-NoClip
LC	LC-Clip
LD	LC-Clip 45deg Boot
LG	LC-Clip 90deg Boot
LE	LC-Clip Short Boot
LH	LC-NoClip Short Boot
LS	LC Uniboot

SB	SC-NoClip
SC	SC-Clip
SD	SC-NoClip Short Boot
SE	SC-Clip Short Boot
SG	SC-Clip 90deg Boot
ST	ST
SU	ST Short Boot

FC	FC
FE	FC Short Boot
OT	OptiTap SC-APC
OV	OptiTip MTP-APC

CONNECTOR 1 / CONNECTOR 2

ML	MTP Elite
MN	MTP Elite Pins
MP	MTP Pins
MT	MTP
MR	MTP 24F Pins
MS	MTP 24F

MC	MTP-Pro Male
MJ	MTP-Pro Female
MJ	MTRJ
MX	MTRJ-Pins
XX	Unterminated

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 -

PRODUCT FAMILY

P	Performa
R	Performa Connectors/Corning Glass-Print Cable
S	Supra
T	Corning Connectors/Corning Glass-Print Cable
U	Ultra
V	Verizon Certified

EXTRAS

P	Pulling Eye, Staggering Connectors
Q	2 Pulling Eye, Staggered
R	Pulling Eye, Config Straight Through
C	Config Straight Through
S	Staggered Connectors
T	Staggered, Config Straight Through

BREAKOUT

E	C-BREAK Single 3 mm
F	C-BREAK Single 2 mm
I	C-BREAK Single 900 μm
C	C-BREAK Y 3 mm
G	C-BREAK Y 2 mm
M	C-BREAK Y 3/2 mm
H	C-BREAK Single 3 mm, OSP
J	C-BREAK Single 2 mm, OSP
K	Reverse C-Term, 3 mm OSP
L	Reverse C-Term, 2 mm OSP

MTP to MTP

S	Type A
X	Type B
P	Type C

UNITS
M- Meters F- Feet I- Inches
LENGTH
As requested

CUSTOMER / OTHER


5	36 in Breakout
8	48 in Breakout
9	12 in Breakout
J	18 in Breakout
B	Tracer Identifier Boot
I	Individual Bag

LABELS / REPORTS

K	1 Label
L	2 Labels
R	Test Report
S	Test Report, 2 Labels
T	Test Report, 1 Label
F	Interferometer Test
E	Corning Low Loss Spec. Test Report

DRAWN BY: K. THOMAS 08/20/2018

APVD BY: A. JENSEN 08/20/2018



C-ENTERPRISES
Connecting Today's Infrastructures

C ENTERPRISES
2445 CADES WAY
VISTA CA 92081
760-599-5111

Product Range	
Product	Description
Performa	Performance cable and connectors
Supra	Corning cable and performance connectors
Ultra	Corning cable and connectors

DIMENSIONS: METRIC [IMPERIAL]			
PROPRIETARY AND CONFIDENTIAL			
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF C ENTERPRISES. NOT TO BE USED, COPIED, OR DISCLOSED WITHOUT WRITTEN PERMISSION. ALL RIGHTS RESERVED.			
TITLE: FIBER PART NUMBER	SIZE: A	DWG. NO.: FIBER-PART-NUMBER	REV: B.3
SCALE: NOT TO SCALE		SHEET 1 OF 1	